



Smart
connections.

Technical Specification

PLENTICORE plus with BMZ HYPERION

	PLENTICORE plus power class		3.0	4.2	5.5	7.0	8.5	10
Input side (DC)	Max. PV power (cos $\varphi = 1$)	kWp	4.5	6.3	8.25	10.5	12.75	15
	Nominal DC power	kW	3.09	4.33	5.67	7.22	8.76	10.31
	Input voltage range ($U_{DCmin} - U_{DCmax}$)	V	120...1000					
	MPP working voltage range ($U_{MPPworkmin} - U_{MPPworkmax}$)	V	120...720					
	Number of DC inputs		3					
	Number of combined DC inputs (PV or battery)		1					
	Number of independent MPP trackers		3					
	DC 3 – battery input optional - Activation code battery available at: shop.kostal-solar-electric.com							
	Working voltage for battery input ($U_{DCworkbatmin} - U_{DCworkbatmax}$)	V	120...500					
	Max. charging current/discharging current at battery input	A	13/13					
Output side (AC)	Rated power, cos $\varphi = 1$ ($P_{AC,r}$)	kW	3.0	4.2	5.5	7.0	8.5	10
	Output voltage ($U_{ACmin} - U_{ACmax}$)	V	320...460					
	Rated output current ($I_{AC,r}$)	A	4.33	6.06	7.94	10.10	12.27	14.43
	Max. output current (I_{ACmax})	A	4.81	6.74	8.82	11.23	13.63	16.04
	Grid connection		3N~, 400V, 50 Hz					
	Standby/standby incl. 24h home-consumption measurement	W	4.5/7.9					
η	Max. efficiency	%	97.1	97.1	97.1	97.2	97.2	97.2
	European efficiency	%	95.3	96.5	96.2	96.5	96.5	96.5
System data	Protection class according to IEC 60529		IP 65					
	Height/width/depth	mm	563/405/233					
	Weight	kg	19.6			21.6		
	Ambient temperature	°C	-20...60					
	Connection technology, DC side		SUNCLIX Stecker					
Directives/Certification ¹⁾		CE, GS, CEI 0-21, CEI10/11, EN 62109-1, EN 62109-2, EN 60529, EN 50438*, EN 50549-1*, ENAEEA, G98, G99, IFS2018, IEC 61727, IEC 62116, RD 1699, RFG, TF3.3.1, TOR Erzeuger, UNE 206006 IN, UNE 206007-1 IN, UTE C15-712-1, VDE 0126-1-1, VDE-AR-N 4105, VJV2018						

	BMZ HYPERION - power class		3 Modules	4 Modules	5 Modules	6 Modules
Systemdaten	Max. Power consumption in connection with PLENTICORE plus 3.0-10 ²⁾	kW	2.0	2.7	3.4	4.0
	Energy content / Usable capacity ³⁾	kWh	9.7/7.5	12.9/10	16.1/12.5	19.3/15
	Usable capacity with PLENTICORE plus 95% DoD ⁴⁾	kWh	7.1	9.5	11.9	14.3
	Number of battery modules		3	4	5	6
	Battery type		Li-Ion NMC			
	Nominal voltage	V	155	207	258	310
	Voltage range	V	134...170	179...227	224...284	268...340
	Interface to inverter		RS485			
	Width/height/depth	mm	751/870/423			
	Weight	kg	107	129	151	173
	Ambient temperature	°C	0...45			
	IP protection class		IP 21			
	Certification / Safety Standard		CE / UN 38.3 / IEC 62619			

Subject to technical changes. Errors excepted. You can find current information at www.kostal-solar-electric.com.

¹⁾ Does not apply to all national annexes, ²⁾ Depending on the max. rated power AC of the inverter (3.0 max. 3.0 kW), ³⁾ According to the battery manufacturer, ⁴⁾ 95% of the usable capacity according to the battery manufacturer